





Metal Faced Circular Access Panel

Non Fire Rated - FF/000/MD/PF/BL/TS/CIR



Description

Metal Faced Circular Access Panel with Picture Frame Surround with an Allen Key Lock to front of door (8mm Square Drive Key Supplied) complete with 3 no Patented Plastic FlipFix Fitting Devices. This panel is Non Fire Rated and can be supplied up to 600mm Diameter and is suitable for use in both WALLS & CEILINGS. Designed for inspection purposes only.

Fitting

Use a circular hole cutter to create an opening 5mm (+5mm) larger than the panel supplied ie 200mm Diameter panel will require opening of 205mm Diameter. Remove door by twisting and place the frame into the opening. Tighten the FlipFix devices from the front with a drill (Torque 3) until the bite is felt at the back. Re-insert the door, lock it and walk away. Be sure to keep the key in a safe place!

Composition & Manufacturing

The FF/000/MD/PF/BL/TS/CIR is manufactured from 0.9mm Zintec Steel (Fully Removable Door) & 1.2mm Zintec Steel (Picture Frame Surround) with a Powder Coat finish – RAL 9010 (30% Gloss White) as standard. Other colours are available upon request although costs may vary.

Dimensions (MM)

Sizes range from 200mm Diameter to 300mm Diameter. Other bespoke sizes are available upon request.

Tests

- This panel is non fire rated.
- This panel is not acoustic rated.
- This panel is not air pressure tested.

find out more at

WWW.FLIPFIX.CO.UK