



## Description

Metal Faced Circular Access Panel with Picture Frame Surround with an Allen Key Lock to front of door (8mm Square Drive Key Supplied) complete with 3 no Patented Metal FlipFix Fitting Devices. Tested to 3 Hour Fire Rated (Maximum Size of 300mm Diameter) this panel is suitable for use in both WALLS & CEILINGS and Designed for inspection purposes only.

## Fitting

Use a circular hole cutter to create an opening 5mm (+5mm) larger than the panel supplied ie 200mm Diameter panel will require opening of 205mm Diameter. Remove door by twisting and place the frame into the opening. Tighten the FlipFix devices from the front with a drill (Torque 3) until the bite is felt at the back. Re-insert the door, lock it and walk away. Be sure to keep the key in a safe place!

## Composition & Manufacturing

The FF/000/MD/PF/BL/SF/CIR is manufactured from 0.9mm Zintec Steel (Fully Removable Door) & 1.2mm Zintec Steel (Picture Frame Surround) with a Powder Coat finish – RAL 9010 (30% Gloss White) as standard. Other colours are available upon request although costs may vary.

## Dimensions (MM)

Standard stock sizes available are 200mm Diameter, and 300mm Diameter. Other sizes are available upon request. Please note sizes over 300mm Diameter will be constructed as per standard products but will not be covered under the current fire test.

## Tests

- This panel is fire rated up to 3 hours.
- This panel is not acoustic rated.
- This panel is not air pressure tested.



### FlipFix Metal Faced Circular 3 Hour Fire Rated (ceiling)

This fire test is applicable for panels up to **300dia**